

GV-650 Video Capture Card



GV-650 D-Type PCI



GV-650 D-Type PCI-E



GV-650 BNC



Specifications

| | |
|---|---|
| Input Type | GV-650 BNC: BNC X 4 |
| | GV-650 D-Type: DB15 X 2 |
| Video Input(s) | 4, 8, 12, 16 Cams |
| Audio Input(s) | 2 Channels |
| Total Recording Rate At 320 X 240 Resolution | 60 fps (NTSC), 50 fps (PAL) |
| Display Rate | 60 fps (NTSC), 50 fps (PAL) |
| Video Resolution - NTSC/PAL | Full D1, Half D1, CIF |
| Compression Format | Geo MPEG4, Geo MPEG4 (ASP), Geo H264, Geo H264 V2 |
| GV-A16 Support | Yes |
| GV-NET Card Support | Yes |
| GV-NET/IO Card Support | Yes |
| Dimensions (W x H) | GV-650 BNC: 144 x 98 (mm) / 5.67 x 3.86 (in) |
| | GV-650 D-Type(PCI & PCI-E) : 144 x 98 (mm) / 5.67 x 3.86 (in) |
| Installation Guide | D-Type (PCI-E) Installing two cards |

Note: GV-650 is currently not compatible with VIA series and ATI series chipset motherboards, and 64-bit Windows operating system.

| Minimum System Requirements For One Card | |
|---|--|
| OS Supported | Windows 2000 / Windows XP / Windows Server 2003 / Windows Vista (Not support 64-bit version of Windows) |
| CPU | Pentium 4-2.4 GHz with Hyper-threading |
| RAM | Windows 2000 / XP: 2 x 512 MB Dual Channels Windows Vista / Server 2003: 2 x 1 GB Dual Channels |
| HDD | 80 GB |
| VGA | ATI Radeon X600 NVIDIA 6200 |
| DirectX | 9.0c |
| Minimum System Requirements For Two Cards | |
| OS Supported | Windows 2000 / Windows XP / Windows Server 2003 / Windows Vista (Not support 64-bit version of Windows) |
| CPU | Pentium 4-2.8 GHz with Hyper-threading |
| RAM | 2 x 1 GB Dual Channels |
| HDD | 160 GB |
| VGA | ATI Radeon X600 NVIDIA 6200 |
| DirectX | 9.0c |

Accessories



4 ports Audio Extension Card



1-8 Cams Video/Audio Cable



9-16 Cams Video Cable