

## GV-800 Video Capture Card



GV-800 D-Type PCI



GV-800 D-Type PCI-E



GV-800 BNC



### Specifications

Input Type	GV-800 BNC: BNC X 4
	GV-800 D-Type: DB15 X 2
Video Input(s)	4, 8, 12, 16 Cams
Audio Input(s)	4 Channels
Total Recording Rate At 320 X 240 Resolution	120 fps (NTSC), 100 fps (PAL)
Display Rate	120 fps (NTSC), 100 fps (PAL).
Video Resolution - NTSC/PAL	Full D1, Half D1, CIF
Compression Format	Geo MPEG4, Geo MPEG4 (ASP), Geo H264, Geo H264 V2
GV-A16 Support	Yes
GV-NET Card Support	Yes
GV-NET/IO Card Support	Yes
Dimensions	GV-800 BNC: 152 x 94 ( mm ) / 5.98 x 3.70 (in)
	GV-800 D-Type: 174 x 98 ( mm ) / 6.85 x 3.86 (in)
Installation Guide	D-Type (PCI-E) Installing two cards

**Note: GV-800 is currently not compatible with VIA series and ATI series chipset motherboards, and 64-bit Windows operating system.**

Minimum System Requirements For One Card	
OS Supported	Windows 2000 / Windows XP / Windows Server 2003 / Windows Vista (Not support 64-bit version of Windows)
CPU	Pentium 4-3.0 GHz with Hyper-threading
RAM	Windows 2000 / XP: 2 x 512 MB Dual Channels Windows Vista / Server 2003: 2 x 1 GB Dual Channels
HDD	80 GB
VGA	ATI Radeon X600 NVIDIA 6200
DirectX	9.0c
Minimum System Requirements For Two Cards	
OS Supported	Windows 2000 / Windows XP / Windows Server 2003 / Windows Vista (Not support 64-bit version of Windows)
CPU	Pentium 4-3.0 GHz Dual Core
RAM	2 x 1 GB Dual Channels
HDD	160 GB
VGA	ATI Radeon X1300 PCI-E NVIDIA GeForce 7300 PCI-E
DirectX	9.0c

### Accessories



4 ports Audio Extension Card



1-8 Cams Video/Audio Cable



9-16 Cams Video Cable