

GV-Reader



GV-READER KEY FEATURES

- GV-Reader 1251: 125kHz Proximity (EM) Card Reader
- GV-Reader 1352: 13.56MHz Mifare Contactless Smart Card Reader, ISO14443A compatible
- Support Wiegand interface
- Support RS485 (9600bps) communication type
- Red / Green LED and Beeper with auto / user mode setup

GV-READER SPECIFICATIONS

CPU		8bit microprocessor
Frequency	GV-Reader1251	125KHz
	GV-Reader1352	13.56MHz for ISO14443A
Wiegand Interface		Wiegand 26 bit, distance 30m (100 ft)
Power		DC 7.5~12V
LED		Red, Green LED
Beeper		Buzzer
RS485		9,600 bps, connect up to 8 GV-Readers
Color		Black
Operating Temperature		0 ~ 65°C / 32 ~ 149°F
Operating Humidity		10 ~90% RH (non-condensing)
Dimension		75 (W) x 115 (H) x 15 (T) mm, with enclosure 35 (T) mm 3 (W) x 4.5 (H) x 0.6 (T) inch, with enclosure 1.38 (T) inch
Weight		150g / 0.33 lbs
Certification		CE, FCC, RoHS
Datasheet		GV-Reader & Card comparison